

## Chapter 3: Understanding NASIS Objects, Tables, and Elements

The first new concept in NASIS 6 is that it is now a client-server application. NASIS 6 software and local database resides on the local computer. Data must be queried from the National Database to populate the Local Database. In order to use data, this chapter will run queries against the national database in order to populate the local database and the selected set to explain the multiple objects and tables. Further information on building the selected set is available in Chapter 4. This chapter will explain the details of NASIS objects and the process of building the NASIS local database on the user's local computer.

### NASIS Data Structure

Chapter 1 introduced the concept of objects and tables in NASIS. NASIS provides the capability to manage two general categories of soil survey data, commonly referred to as the Aggregated Data and the Point Data. The Aggregated Data structure includes a set of objects and related tables needed to document the soil map units and components and associate the map units with a soil survey area legend. The Legend/Map Unit/Data Mapunit Data Structure Diagram shows the objects and tables that make up the Aggregate Data.

The Point Data structure includes the objects and tables needed to manage the site and pedon descriptions collected in the field. The Site Association/Site/Pedon/Transect Data Structure Diagram shows the objects and tables associated with the Point data.

Downloadable versions of these data structure diagrams can be found on the NASIS web site (<http://soils.usda.gov/technical/nasis/documents/index.html>). The remainder of this chapter will focus on the Legend/Map Unit/Data Mapunit Data Structure and the NASIS Aggregated Data.


### NASIS Aggregate Data

The major objects of the aggregated data are the “**Area Type**”, “**Legend**”, “**Mapunit**” and “**Data Mapunit**”. A new object has been introduced with the release of NASIS 6.0. The **Mapunit** Object contains the *mapunit* table that was previously contained within the Legend Object. The MLRA concept of updating soil surveys provided the impetus to move the mapunit table into a new object, thereby allowing a map unit to be shared across multiple legends. This move facilitates the seamless join of map units, with its unique national map unit symbol, across the country.

## The Area Type Object


NASIS stores more than just traditional soil survey areas. Because there are several kinds of areas, they are organized by *area type*.

In the Tables Explorer, open the Area Type table by double-clicking on Area Type or highlighting the table and choosing Open on the Explorer menu or right click on the table and chose Open. The table should be empty, if not then clear the Selected Set using the whisk broom icon found on the NASIS toolbar or Clear Selected Set from the NASIS menu.



### Querying Area Types

Choose the Query Explorer and right click on the national query named “Area by area type name and area name and NASIS Site” and **Run Against Local Database**:



## NASIS User Guide

**Selections for Running Query Area by area type name and area name and NASIS site**

Target Tables: ☐ NASIS Site ☒ Area Type ☐ Area

Area Type Name: \*

Area Name: \*

NASIS Site Name: NSSC Pangaea

Run Cancel

☐ Check Out

Enter the parameters as presented in the image above –  
 Choose Area Type as the Target Table,  
 Enter an asterisk (\*) for the Area Type Name and  
 Enter an asterisk (\*) for the Area Name, and  
 Enter “NSSC Pangaea” as the NASIS Site name (or “\*pan\*”).

The data within the Area Type Object is loaded into the local database at the time of Initialization and is refreshed with changes when the “Refresh local database” is chosen. It is not necessary to run this query against the national database. The result should be 20 rows of Area Type data.


Area Type						
	Area Type Name	Area Type NASIS Site	NASIS Group		Object Last Upda...	
	Area Type Name	NASIS Site Name	NASIS Group Name	Object Last Updated	NASIS User Name	
	Bureau of Land Management Administered Land	NSSC Pangaea	Standard Area Types	02/10/1998 13:45:50	Kelsea, Russell J.	
	Climate Factor Area	NSSC Pangaea	Standard Area Types	05/16/1997 16:01:01	Kelsea, Russell J.	
	Country	NSSC Pangaea	Standard Area Types	02/09/2009 19:13:22	Fortner, Jim	
	County or Parish	NSSC Pangaea	Standard Area Types	03/18/2009 07:24:50	Fortner, Jim	
	Land Resource Region	NSSC Pangaea	Standard Area Types	05/16/1997 16:01:01	Kelsea, Russell J.	
	Legacy MLRA Soil Survey Area	NSSC Pangaea	Standard Area Types	09/04/2008 12:34:23	Fortner, Jim	
	Military Reservation	NSSC Pangaea	Standard Area Types	07/25/2006 15:21:39	Finnell, Paul R.	
	MLRA	NSSC Pangaea	Standard Area Types	02/12/2007 12:22:27	Fortner, Jim	
	MLRA Soil Survey Area	NSSC Pangaea	Standard Area Types	06/03/2009 10:11:15	Fortner, Jim	
	MLRA Soil Survey Regional Office Area	NSSC Pangaea	Standard Area Types	09/04/2008 12:36:04	Fortner, Jim	
	National Forest System Land	NSSC Pangaea	Standard Area Types	04/12/2004 10:20:29	Fortner, Jim	
	National Park System Land	NSSC Pangaea	Standard Area Types	04/06/2009 05:21:33	Fortner, Jim	
	Non-MLRA Soil Survey Area	NSSC Pangaea	Standard Area Types	05/01/2009 09:14:46	Fortner, Jim	
	Physiographic Division	NSSC Pangaea	Standard Area Types	05/28/2002 07:14:25	Fortner, Jim	
	Physiographic Province	NSSC Pangaea	Standard Area Types	03/05/1998 10:32:30	Kelsea, Russell J.	
	Physiographic Section	NSSC Pangaea	Standard Area Types	03/05/1998 10:32:40	Kelsea, Russell J.	
	Rainfall Factor Area	NSSC Pangaea	Standard Area Types	04/12/2005 13:10:21	Fortner, Jim	
	State or Territory	NSSC Pangaea	Standard Area Types	03/18/2009 07:21:20	Fortner, Jim	
	USGS 15 Minute Quadrangles	NSSC Pangaea	Standard Area Types	09/30/1998 15:39:34	Kelsea, Russell J.	
	USGS 7.5 Minute Quadrangles	NSSC Pangaea	Standard Area Types	10/28/2008 05:43:28	Fortner, Jim	

The area types stored in NASIS appear. NASIS stores National Park Service Lands, National Forest Lands, Military Reservations, Land Resource Regions, and many more. Notice that in NASIS, climate and rainfall factor areas, and political and physiographic areas are all stored, in addition to soil survey areas.



## The Legend Object

The soil survey area is independent from the legend. The following illustration provides a visual explanation of the separation of area from legend.




### *Separation of Soil Survey Area and Legend*

One area can have multiple legends (a 1 to many relationship). For example, Pike County, Illinois can have both an out-of-date legend and an updated legend. Each legend, however, can be part of only one survey area (Pike County, Illinois). There are only two National Area Types in which legends are linked, the **Non-MLRA Soil Survey Area** and the **MLRA Soil Survey Areas**.

Because the area type object and the legend object are independent, navigating to the legend for a particular survey area requires a leap across object boundaries from the **Area** table to the **Legend** table, as shown in the following figure.


This figure below presents both the Area Type and the Legend Objects. Object boundaries are marked by the larger black line and larger red line rectangles. The purple lines between tables in the two objects indicate crossing points for moving from one object (Area Type) to another (Legend).



Legends are stored only for MLRA soil survey area and Non-MLRA soil survey area types.

### *Locating object boundaries*

In the Tables Explorer, open the **Legend** table.




The table is empty because data was loaded into the Area Type Object but not into the Legend Object. The query was **Run Against the Local Database** to load the 20 national Area Types into the selected set. To load data into the Legend Object the data must be queried from the national database. Since Areas are independent of the Legend Objects, the Legends must be queried from the National Database to populate the Local Database and then queried from the Local Database into the Selected Set to view data in the Legend table.

A short digression is required to load the Local Database with data before proceeding with this chapter. This exercise will take about 30 minutes and will load the Local Database with data for future use.

## Using a query to load data from the national database


Select the National query: “Area/Lmapunit/Mapunit/Datamapunit by Area Symbol”. This query will be run using the option “Run Against National Database”.



Choose “Legend” as the target table. Only one Target Table is allowed for the national queries. Area Type is not an option since the Area Type object is preloaded into the Local Database.

Select the state of interest, in this example all of the legends in Kansas will be loaded using the two character state code with a wildcard “KS\*”. Choose any state.


It will take approximately two minutes to run the query and display the selected surveys in the “Local Database Setup”.



Click on the “Accept” button to choose the selected data to download to the local database. This may take 30 minutes (25 mb) or more to download the data depending on the size of the dataset and the speed of the internet connection. This query will retrieve all the Legends, Mapunit, Datamapunits, linked Pedons and linked Sites for the selected state.


# NASIS User Guide

Although a significant amount of time is used to download large datasets, the intent is to download this data once. The local database will be subsequently refreshed on a regular basis to retrieve any edits posted to the national database by other users.



Upon completion, the Status Messages panel will identify the data downloaded from the National database. The object tabs can be reviewed for data loaded into the local database.

Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS193	Thomas County, Kansas	687757	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS165	Rush County, Kansas	459514	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS125	Montgomery County, Kansas	416947	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS153	Rawlins County, Kansas	684646	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS059	Franklin County, Kansas	369427	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS107	Linn County, Kansas	387936	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS121	Miami County, Kansas	377895	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS031	Coffey County, Kansas	418605	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS163	Rooks County, Kansas	572851	published	MLRA05_Office	Kansas
Local	NSSC Pangaea	Non-MLRA Soil Survey Area	KS133	Ness County, Kansas	369767	published	MLRA05_Office	Kansas


**Status Messages**


Number of rows loaded into Legend = 0  
Number of related rows loaded = 0

Preparing query "Area/Lmapunit/Mapunit/Datamapunit by Area Symbol" ...  
Running national query for target table "Legend" ...  
Number of data objects found:  
Legend: 105  
Mapunit: 12993  
Data Mapunit: 4985  
Site: 848  
Pedon: 848  
Transect: 133




## Loading the Legend table

Now that data is populated into the Local Database, return to the **Legend** table. As a reminder, the local database has now been populated with data. The Local Database must now be queried to populate the selected set – the Legend table.



Return to the Area Type tab and select an Area from the list within the Non-MLRA Soil Survey Area. For this exercise to work properly, the user must select an Area that was downloaded from the National Query and is available in the Local Database.

For this example, Saline County, Kansas has been selected:




## Crossing from area table to legend table


Returning to the explanation of data base objects, the next step is to populate the selected set. There are two methods of loading the **Legend** data for Saline County, Kansas “Non-MLRA Soil Survey Area”. Either:

1. Run a query – “Run Against the Local Database”, or
2. Use the “Load Related for Selected Rows”.


For this exercise the “Load Related for Selected Rows” will be used. In this example, the KS169 “Saline County, Kansas” row is highlighted and from the Table Editor menu the “Load Related for Selected Rows” is chosen:



A choice list box will appear containing those tables that are related to the Area table. For this example choose the “Legend” table.




The Status Messages panel will identify the data loaded from the local database into the selected set for the Legend table:



To review this process:

1. The data in the Area Type object is preloaded into the *Local Database* at the time of the database “initialization”.
2. A query was “Run Against Local Database” to load the national Area Types into the *selected set*.
3. A query was “Run Against National Database” to download a state dataset to populate the local database.
4. Returning to the Area Type table, the Non-MLRA Soil Survey Area table was opened, a survey from the list was highlighted and the “Load Related for Selected Rows” command was used to load the Legend that is related to the chosen Area.
5. A second method would be to run the same query using “Run Against Local Database” to populate Legend data into the selected set.
6. This example crosses the Area Type Object and the Legend Object by loading the Legend(s) for the selected Area.



Return to the Legend table tab. The **Legend** table is now populated with the Saline County, Kansas Non-MLRA Soil Survey Area (or whichever legend the user has chosen). Using the Load Related function, the Area Type Object and the Legend Object has been “crossed”.

Area						
	Area Type NASIS Site Name	Area Type Name	Area Symbol	Area Name	Area Acres	MLRA Office
▶	NSSC Pangaea	Non-MLRA Soil Survey Area	KS169	Saline County, Kansas	461645	salina, ks

Open the Legend child tables by clicking on the plus (+) sign on the left side of the row in the Legend table or by “double-clicking” on the space to the left of the plus (+) sign.

T Area Type T Legend Local Database								
Area								
Area Type NASIS Site Name	Area Type Name	Area Symbol	Area Name	Area Acres	MLRA Office	Legend Description ↑	Survey Status ↑	
NSSC Pangaea	Non-MLRA Soil Survey Area	KS169	Saline County, Kansas	461645	salina, ks	Detailed Soil Map Legend	published	
Legend Mapunit Legend Area Overlap Legend Certification History Legend Export Certification History Legend Text								
Mapunit								
Seq	Mapunit Symbol	Total Acres	National Mapunit Symbol	Mapunit Name ↑	Mapunit Status	Record Last Updated		
	Ba	4045	1zhr	BAVARIA-DETROIT COMPLEX, RARELY FLOODED	additional			
	3250	4045	tmh6	Bavaria-Detroit complex, rarely flooded	correlated			
	113BR	241	1zip	BRIDGEPORT SILT LOAM, RARELY FLOODED	additional			
	2310	241	tmh7	Bridgeport silt loam, rarely flooded	correlated			
	Cd	2173	1zhs	CASS FINE SANDY LOAM, OCCASIONALLY FLOO...	additional			
	3521	2176	tmh8	Cass fine sandy loam, occasionally flooded	correlated			
	Ce	8659	1zht	CLIME SILTY CLAY LOAM, 2 TO 6 PERCENT SLOPES	additional			
	4555	8441	tmh9	Cline silty clay loam, 3 to 7 percent slopes	correlated			
	113CM	48	1ziu	CLIME SILTY CLAY, 3 TO 6 PERCENT SLOPES	additional			
	4570	48	tmha	Cline silty clay, 3 to 7 percent slopes	correlated			
	Co	6420	1zhu	COZAD SILT LOAM, 0 TO 2 PERCENT SLOPES, RA...	additional			
	3715	6419	tmhb	Cozad silt loam, rarely flooded	correlated			


The Legend Object, displayed above, contains the child tables used to manage the map units within the specific soil survey area legend. In a later lesson the columns of the tables in the Legend Object will be examined. This lesson focuses exclusively on navigating objects and understanding the NASIS structure.

Examine each column in the Legend table scrolling to the right to view all columns. The Legend table stores the legend description, geographic applicability, and certification status. Remember from Chapter 2 to use the View Information button to obtain information about any table or data element. The two fields “survey status” and “correlation date” are now obsolete fields and no longer available for editing. The update of soil surveys has focused the emphasis from the status of “Legends” to the status of “Mapunits”.

## The Mapunit Object

The Area Type Object has been loaded and reviewed.  
The Legend Object has had a survey loaded and reviewed.

The Mapunit Object is a new object in NASIS 6.0. The Mapunit Object was created to manage map units across multiple survey legends. The boundaries between these independent objects will be crossed using the Load Related command to load data into the Mapunit Object.




### Crossing Between Legend, Mapunit, and Data Mapunit Objects


The Mapunit Object manages the map unit providing the map unit documentation and the links to the map unit data. Return to NASIS to load data into the Mapunit Object from a selection in the Legend Object.

## NASIS User Guide

In this step, in the Legend Mapunit table, the “Lancaster-Hedville complex, 3 to 20 percent slopes” mapunit is highlighted and the “Load Related for Selected Rows” is chosen from the Table Editor menu.




The Mapunit table is chosen from the parameter choice list:



This loads the specific map unit into the “selected set”.

The next step is to view the map unit. The Mapunit table is opened from the Explorer menu and the Mapunit Object (parent and child tables) is viewed beginning with the Mapunit table:



The screenshot shows the NASIS software interface with the 'Mapunit' table selected in the Explorer menu. The main window displays the 'Mapunit' table with columns: Mapunit Name, Kind, Status, National Mapunit Symbol, and Farm Class. A record for 'Lancaster-Hedville complex, 3 to 20 percent slopes' is visible. Below the main table, there are tabs for 'Correlation', 'Mapunit History', 'Mapunit Text', 'Mapunit USFS Ecological Classification', and 'Mapunit USFS Interpretation'. The 'Data Mapunit' table is also visible, with columns: Seq, DMU Description, Data Mapuni..., Rep D..., and Constituent Acres. A 'Status Messages' window at the bottom shows a message about the selected mapunit.

Mapunit Name	Kind	Status	National Mapunit Symbol	Farm Class
Lancaster-Hedville complex, 3 to 20 percent slopes	complex	correlated	tmht	0

Seq	DMU Description	Data Mapuni...	Rep D...	Constituent Acres
1				

Review the data contained within the mapunit table and its various child tables. There are five child tables:


- The Correlation table contains the links to the mapunits' data.
- The Mapunit History table documents the map unit's correlation events.
- The Mapunit Text stores documentation on the map unit.
- The two USFS tables are designed for future use.



## The Data Mapunit Object

The Area Type Object has been loaded and reviewed.  
 The Legend Object has had a survey loaded and reviewed.  
 The Mapunit Object has had a mapunit loaded and reviewed.

The Data Mapunit Object is designed to capture the soil properties, qualities and interpretations for each component within the map unit concept. The boundaries between these independent objects will be crossed using the Load Related command to load data into the Data Mapunit Object.




Returning to NASIS, in the Correlation table, notice that one record is designated a representative data mapunit (Rep DMU) and one is not designated by the check mark in the “Rep DMU” column.


Seq	DMU Description	Data Mapunit ID	Rep DMU
041LA		64179	<input checked="" type="checkbox"/>
169LH		66144	<input type="checkbox"/>

Highlight the row designated as the representative data mapunit.  
 Choose the Editor Toolbar icon “Load Related for Selected Rows” or from the Table Editor menu.

The choice list appears. Select Data Mapunit.




A message appears in the message panel indicating that one row was added to the selected set. An additional 222 related rows are also added to the selected set.



This process loads the specific DMU into the "Selected Set". The data is available and now must be viewed.

## NASIS User Guide


To review the data open the Data Mapunit table from the Tables Explorer. Review the child tables associated with the Data Mapunit Object.



The screenshot shows the NASIS Tables Explorer interface. The 'Data Mapunit' table is selected, and its child tables are displayed below it. The child tables include 'Component', 'Data Mapunit Certification History', 'Data Mapunit Crop Yield', and 'Data Mapunit Text'. The 'Component' table is expanded, showing a list of components with columns for 'Seq', 'Low', 'RV', 'High', 'Component Name', 'Local Phase', 'Taxon Kind', and 'Major Component'.

Seq	Low	RV	High	Component Name	Local Phase	Taxon Kind	Major Component
70				Lancaster	C	series	<input checked="" type="checkbox"/>
30				Hedville	C	series	<input checked="" type="checkbox"/>
0	0	1		Aquolls	M	taxon abov...	<input type="checkbox"/>

**NOTE:** This entire exercise could have been completed by loading all data using a single query and choosing the appropriate Target Tables:



The screenshot shows the 'Selections for Running Query' dialog box. The 'Target Tables' section has checkboxes for 'Area', 'Legend', 'Legend Mapunit', 'Mapunit', 'Correlation', and 'Data Mapunit'. The 'Data Mapunit' checkbox is checked. The 'Soil Survey Symbol Matches' section has a text box containing 'KS169'. The 'Run' button is highlighted.

Selections for Running Query Area/Lmapunit/Mapunit/Datamapunit by Area Symbol

Target Tables:

- ☒ Area
- ☒ Legend
- ☐ Legend Mapunit
- ☒ Mapunit
- ☐ Correlation
- ☒ Data Mapunit

Soil Survey Symbol Matches: KS169

Run Cancel

☐ Check Out

Using this query would load all data associated with the specific survey area. The purpose of this exercise was to show the method of using the "Load Related" command. "Load Related" allowed the loading of specific rows of data.

## **Summary:**

The database manages tables using “Objects” which are used to group tables of similar data. There is independence between the database objects. This independence allows objects to be linked to one another.

- A Data Mapunit stores the soil properties, qualities and interpretations for a given map unit concept.
- A Data Mapunit can be linked to multiple Mapunits (or a single map unit).
- A Mapunit can be linked to multiple Legends (or a single legend).
- A Legend is linked to only one Area.

The information in the Area Type Object is downloaded to the Local Database upon database initialization.

The National Database must be queried to populate the Local Database with the Legend, Mapunit and Data Mapunit information.

The Local Database is then queried to populate the Selected Set.

The Selected Set is used to view, analyze, edit and report soils information.

The Load Related command on either the Table Editor menu or the icon on the Table Toolbar can be used to load data from one database object into another database object.